


Nylon coated shielded wire FVNP

NYLON JACKET WIRE



Insulation: PVC

Conductor: Tinned Copper

Temperature Range: -65°C ~ + 105°C

Rated Voltage: 600V

O.D. Tolerance: ±0.1mm

Colour: White-Blue-Red-Black-Brown-Yellow-Green-Transparent-Yellow/Green

Used plan low voltage wiring, high-speed road inductance wiring, lighting lamp, high popl lamp in the road and so on.

NYLON JACKET WIRE

PRODUCT PARAMETER

Conductor		Insulation			Packing
Sectional Area mm ²	Conductor Construction NO.X Φ mm	Insulation Thickness mm	Pleach Thickness mm	Outer Diameter mm	M/coil
0.2	12 x 0.15	0.35	0.15	2.10	200
0.3	16 x 0.15	0.35	0.15	2.20	200
0.4	23 x 0.15	0.35	0.15	2.40	200
0.5	28 x 0.15	0.35	0.15	2.50	200
0.6	19 x 0.20	0.35	0.15	2.50	200
0.75	19 x 0.23	0.35	0.15	2.65	200
1.0	19 x 0.26	0.35	0.15	2.80	200
1.2	19 x 0.28	0.40	0.15	3.00	100
1.5	19 x 0.32	0.40	0.15	3.20	100
2.0	19 x 0.37	0.40	0.15	3.45	100
2.5	49 x 0.26	0.40	0.15	4.05	100
3.0	49 x 0.28	0.45	0.15	4.20	100
4.0	77 x 0.26	0.45	0.15	4.80	100
5.0	98 x 0.26	0.45	0.18	5.20	100
6.0	77 x 0.32	0.50	0.18	5.60	100
8.0	98 x 0.32	0.50	0.18	6.10	100
10.0	126 x 0.32	0.50	0.18	6.70	100
13.0	133 x 0.36	0.60	0.22	7.60	100
16.0	209 x 0.32	0.60	0.22	8.40	100
20.0	247 x 0.32	0.60	0.22	9.00	100
25.0	209 x 0.39	0.60	0.22	9.80	100
35.0	285 x 0.39	0.60	0.22	11.0	100